

R20 SR HPR film

features & benefits

Reflective solar control and privacy film that offers significant improvement of working conditions due to a high reduction in solar heat gain and air-conditioning costs.

The film acts as a 'one way mirror' offering privacy during daylight hours. Also reduces glare significantly with anit-UV protection which helps to reduce fading of textiles, furniture, and works of art. It's also scratch resistant allowing for easy cleaning.

Applicable as Decor and Design or Privacy film, also available as Safety film for interior installation.

Technical data according to EN410 and EN 673	4mm Single	0.837	4/16/4mm double
Solar Energy Transmission	12%		12%
Solar Energy Reflection	51%		46%
Solar Energy Absorption	36%		42%
Visible Light Transmission	16%		17%
_	10/0		17/0
Visible Light Reflection (external)	58%		61%
Visible Light Reflection (Internal)	59%		63%
Ultraviolet Transmission		<1%	
Ultraviolet Rejection		>99%	
g value	0.20		0.30
shading coefficient	0.23		0.36
total solar energy rejected	80%		69%
glare reduction	82%		83%
u value, single glazing (w/m².K)	5.3		-
U value, double glazing, air filled (w/m².K)	-		2.6
Emissivity		0.71	
Thickness without Liner		45µ	
Film Colour		Silver	
Installation Position	_	Interior	
Warranty		7 years	
Installation Notes - Use Film On for Installation			